

TRAXXION DYNAMICS

FORK CHECKLIST

CUSTOMER: _____

DISASSEMBLY/INSPECTION:

- _____ DISASSEMBLE UNITS
- _____ CHECK FORK TUBE AND SLIDER FOR DAMAGE
- _____ CHECK SEALS FOR LEAKAGE
- _____ CHECK ADJUSTERS FOR DAMAGE AND FUNCTION

REVALVE CARTRIDGE:

- _____ SURFACE ALL PISTONS
- _____ CHANGE REBOUND DAMPING
- _____ CHANGE COMPRESSION DAMPING
- _____ INSPECT VALVING AT PISTON FACES
- _____ INSPECT CHECK PLATES FOR ACTION
- _____ INSURE PROPER SPACING OF STACKS
- _____ SMALL DOTS OF RED LOC-TITE

REVALVE DAMPING ROD:

- _____ BRAZE AND DRESS AS NEEDED
- _____ DRILL AND DRESS AS NEEDED
- _____ SET EMULATOR SPRINGS _____ turns

REASSEMBLY:

- _____ USE NEW CRUSH WASHER, IF NECESSARY
- _____ GREASE NEW SEALS
- _____ MAKE SPRING PRELOAD SPACERS _____ mm preload
- _____ MAKE SURE SPACERS ARE EQUAL, DEBURR BOTH ENDS
- _____ BLEED FORK THOROUGHLY
- _____ SET OIL LEVEL _____ mm _____ (oil)
- _____ INSTALL SPRINGS _____ (rate)

INSPECTION:

- _____ SET PRE-LOAD ADJUSTERS _____ spaces showing
- _____ INSURE DAMPING ADJUSTERS ARE EQUAL C(out) _____ R(out)
- _____ CHECK DAMPING ACTION
- _____ CLEAN BOTH FORKS THOROUGHLY
- _____ APPLY DECALS

TECHNICIAN _____

DATE _____

PARTS: _____

LABOR: _____

INSPECTED BY _____

DATE _____